# FN1-043XX0AGW Range

# 0.43" (11 mm) Single Digit 7 Segment Display

## Features:

- High segment intensity
- Wide viewing angle
- · Range of colours
- · Grey face colour
- White segment colour

# Available options:

- Alternative face and segment colour
- Alternative font
- Long terminal pins
- Alternative emitting colour
- Low current version

## Font design

Product not shown actual size



## Electro / Optical Characteristics - $I_F$ = 20 mA (\* HE Blue - $I_F$ = 10 mA) $T_a$ = 25° C

Part Number Common Cathode	Part Number Common Anode	Emitting Colour	Wavelength Peak λ <sub>P</sub>	Forward Voltage V <sub>F</sub>		Luminous Intensity I <sub>V</sub>	
				typical	max	min	typical
FN1-0431L0AGW	FN1-0432L0AGW	GaAlAs Red	660	1.85	2.00	-	15
FN1-043130AGW	FN1-043230AGW	HE Red	640	2.05	2.50	-	5
FN1-0431Y0530AGW	FN1-0432Y0530AGW	Yellow	591	2.05	2.40	-	30
FN1-043120AGW	FN1-043220AGW	Green	568	2.10	2.50	-	9
FN1-0431B050AGW	FN1-0432B050AGW	* HE Blue	465	3.70	4.00	-	6
FN1-0431B010AGW	FN1-0432B010AGW	Blue	428	3.80	4.50	-	4
Units			nm	V		mcd / seg. (digit average)	

## **Maximum Ratings** $T_a = 25^{\circ} \text{ C}$ - Derate above 25° C

Characteristic	Condition		Symbol	Rating	Units
Pulse Forward Current	0.1 duty cycle @ 1KHz	(HE Blue)	I <sub>FP</sub>	100 (35)	mA
DC Forward Current		(HE Blue)	I <sub>F</sub>	25 (15)	mA
Reverse Voltage	$I_R = 10 \mu A$		$V_{R}$	5	V
Operating Temperature			$T_{opr}$	- 25 to + 80	°C
Storage Temperature			T <sub>stg</sub>	- 30 to + 85	° C
Lead soldering temperature 1.6 mm from body - max 3 seconds				260	° C

#### Note

Industry standard procedures regarding static must be observed when handling product produced with blue die material.




Issue 03


## **Package Outline**

# 1.00 PIN 1 24 5 10.92 18.90 24\*6 ø1.60 12.60 — 7.80 Ø0.50 +0.5/-0

## **Common Cathode**



## **Common Anode**



#### Tolerance ± 0.25 mm unless stated



No representation, warranty, responsibility or liability is or will be accepted by Forge Europa Limited in relation to the accuracy or completeness of any information it provides. It is the responsibility of the customer to verify the suitability of the product for its application. All design work supplied by Forge Europa Limited is to be assumed confidential and is the sole property of Forge Europa Limited. It must not be used, copied or disclosed to any third party without the prior written consent of Forge Europa Limited. All contracts are subject to Forge Europa Limited's General Terms and Conditions of Trading which can be found at www.forge-europa.co.uk

Issue 03

Page 2 of 2 09.15