## FND-757XX00GW Range

# 3.1" ( 80 mm ) 5 x 7 Dot Matrix Display

### Features:

- High dot intensity
- Wide viewing angle
- · Range of colours
- · Grey face colour
- White dot colour

## Available options:

- · Alternative face and dot colour
- Cropped terminal pins
- Alternative emitting colour
- Low current version

## Dot layout

Product not shown actual size



## Electro / Optical Characteristics - $I_F = 20 \text{ mA}$ (\* HE Blue - $I_F = 10 \text{ mA}$ ) $T_a = 25^{\circ} \text{ C}$

Part Number Column Cathode	Part Number Column Anode	Emitting Colour	Wavelength Peak λ <sub>P</sub>	Forward Voltage V <sub>F</sub>		Luminous Intensity I <sub>V</sub>	
				typical	max	min	typical
FND-7571L00GW	FND-7572L00GW	GaAlAs Red	660	3.70	4.00		72
FND-7571300GW	FND-7572300GW	HE Red	640	4.10	5.00		18
FND-7571Y05300GW	FND-7572Y05300GW	Yellow	591	4.10	4.80		112
FND-7571200GW	FND-7572200GW	Green	568	4.20	5.00		36
FND-7571B0500GW	FND-7572B0500GW	* HE Blue	465	7.40	8.00		23
FND-7571B0100GW	FND-7572B0100GW	Blue	428	7.60	9.00		15
Units			nm	V		mcd / dot (matrix average)	

### **Maximum Ratings** $T_a = 25^{\circ} C$ ( Derate above 25° C )

Characteristic	Condition		Symbol	Rating	Units
Pulse Forward Current	0.1 duty cycle @ 1KHz	( HE Blue )	$I_{FP}$	100 (35)	mA
DC Forward Current		(HE Blue)	Ι <sub>F</sub>	25 (15)	mA
Reverse Voltage $I_R = 10 \mu A$			$V_{R}$	5	V
Operating Temperature			$T_{opr}$	- 25 to + 80	° C
Storage Temperature			T <sub>stg</sub>	- 30 to + 85	° C
Lead soldering temperature 1.6 mm from body - max 3 seconds				260	° C

#### Note

Industry standard procedures regarding static must be observed when handling product produced with blue die material.





# FND-757XX00GW Range


# 3.1" ( 80 mm ) 5 x 7 Dot Matrix Display


## **Package Outline**

### **Column Cathode**










### **Column Anode**



Tolerance ± 0.25 mm unless stated

5.08\*6=30.48



No representation, warranty, responsibility or liability is or will be accepted by Forge Europa Limited in relation to the accuracy or completeness of any information it provides. It is the responsibility of the customer to verify the suitability of the product for its application. All design work supplied by Forge Europa Limited is to be assumed confidential and is the sole property of Forge Europa Limited. It must not be used, copied or disclosed to any third party without the prior written consent of Forge Europa Limited. All contracts are subject to Forge Europa Limited's General Terms and Conditions of Trading which can be found at www.forge-europa.co.uk

Issue 03